

HYPERTURN 65



ORDER NOW

TECHNICAL DATA

WORK AREA

MAIN SPINDLE

COUNTER SPINDLE

TOOL TURRET

GENERAL DATA

Travel in X/Y/Z

z.B. HT 65 DT-1000: X1/X2:260/210,
Z1/Z2/Z3:800/800/800, Y1/Y2:100(+/-50) mm

Bar diameter

65 (76,2/95) mm

Swing over bed

660 mm

Rapid motion speeds in X/Y/Z

30/12/30 m/min

TECHNICAL DATA

WORK AREA

MAIN SPINDLE

COUNTER SPINDLE

TOOL TURRET

GENERAL DATA

Max. speed

0-5000 (4000/3500) U/min

Max. drive power

29 (37) kW

Max. torque

250 (360) Nm

TECHNICAL DATA

WORK AREA

MAIN SPINDLE

COUNTER SPINDLE

TOOL TURRET

GENERAL DATA

Max. speed

0-5000 (4000/3500) U/min

Max. drive power

29 kW

Max. torque

250 Nm

TECHNICAL DATA

WORK AREA

MAIN SPINDLE

COUNTER SPINDLE

TOOL TURRET

GENERAL DATA

VDI size

30 (40)

Number of tools

2/3×12

Driven tools

2/3×12

Max. speed

0-5000 (4500) U/min

Max. drive power

6,7 kW

Max. torque

25 Nm

TECHNICAL DATA

Dimensions (LxWxH)

5060/5300 x 2850 x 2360 mm

Machine weight

ca. 9500 kg

WORK AREA

MAIN SPINDLE

COUNTER SPINDLE

TOOL TURRET

GENERAL DATA



Main Menu

About Us

Products

Services

Blogs

Contact us

Our Products

CNC Machining Solutions

Cutting Tools

Metrology Solutions

3-D printing

Diamond Tooling Solution

Industrial Training

Useful Information

📍 WHP2-Block-A Commercial,13-0, P2AG-

H03 Office Saih Shuaib 3

Dubai, United Arab Emirates

PO Box 127104 (U.A.E)

📞 +971-54-768-7456

✉️ info@taqneea.com